

500-729  
Rec'd PCT/PTO 06 JUL 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 July 2003 (31.07.2003)

PCT

(10) International Publication Number  
WO 03/062570 A1

(51) International Patent Classification<sup>7</sup>: E05B 27/00, 27/10, 15/14 (74) Agent: EHRNER & DELMAR PATENTBYRÅ AB; Box 103 16, S-100 55 Stockholm (SE).

(21) International Application Number: PCT/SE03/00074 (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 17 January 2003 (17.01.2003) (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0200182-4 23 January 2002 (23.01.2002) SE


(71) Applicant (for all designated States except US): WINLOC AG [CH/CH]; Baarerstrasse 43, CH-6304 Zug (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): WIDEN, Bo [SE/SE]; Box 37, S-644 21 Torshälla (SE).

[Continued on next page]

(54) Title: HIGH SECURITY LOCK AND KEY BLADE COMBINATION



(57) Abstract: A high security cylinder lock (1) and key (2) combination comprising a cylindrical shell (140), a key plug (130) which is rotatably mounted in the shell (140), a longitudinal key slot (100) in the key plug, and at least one locking tumbler assembly cooperating with a key being inserted into the lock. The locking tumbler assembly comprises a pair of independently movable tumbler segments (113, 114) which are positionable in different elevational positions in a common cavity.

WO 03/062570 A1